

Now...a budget-priced Stereo Diskchanger that performs like a champion



WEBCOR "CUSTOM" Hi-Fi Stereo Diskchanger

GOLDEN BEIGE AND BROWN

MODEL 1041-1 . . . Astatic ceramic stereo cartridge with turnover styli. .7 mil diamond tip for stereo and standard microgroove records. 3 mil sapphire tip for 78 rpm records. Webcor precision-built motor. Output: .4 volts per channel at 1,000 cycles.

MODEL 1041-21 . . . GE stereo magnetic cartridge. .7 mil diamond tip for stereo and standard microgroove records. 4-pole, 4-coil motor. Output: 10 millivolts per channel at 1,000 cycles. Dual channel pre-amplifier required.

MODEL 1041-27 . . . Has two plug-in heads with standard $\frac{1}{2}$ " mounting center to accommodate most stereo cartridges. $\frac{7}{8}$ " spacing to rear of mounting holes and $\frac{1}{2}$ " in front of mounting holes. 1" wiring on pins for easy cartridge hook-up. 4-pole, 4-coil motor.

Also available with attractive metal base pan. Model TS-1042-1 or Model TS-1042-21.

Installation: 2 fono cables with 2 pin plugs. AC plug. Pickup and AC leads 36" from clamp. Template provided. 110-120 volts. 60 cycle AC. Minimum mounting board dimensions: $13\frac{1}{2}$ " deep x $14\frac{1}{16}$ " wide x $9\frac{1}{2}$ " high. Above and below dimensions: $5\frac{1}{2}$ " above, 4" below.

SPECIAL WEBCOR FEATURES

Jam-proof mechanism—"Torsion spring" action permits moving tone arm at any time without jamming or damaging changer.

Exclusive anti-rumble ribs—Scientifically designed and constructed to absorb vibration for negligible rumble.

Positive manual—Permits manual record play without activating automatic change cycle.

Speed Selector—Changer plays all four speeds and both stereo and standard records. 10" and 12", $33\frac{1}{3}$ rpm records may be intermixed in any sequence.

Balanced Tone Arm—Lightweight and free swing. Adjustable stylus pressure 5 to 11 grams.



Your Webcor
dealer will be
glad to
demonstrate.
See him now.